

Products available from Custom Door Components™

Particle Core: LD-1 and LD-2, Cut-to-size

- Sanded thickness from 1-1/8" to 2-1/4"

Banded Particle Core: Sizes from 2/0 x 7/0 through 4/0 x 9/0

- Sand to 1.500 or 1.625

Crossbanded Particle Core: Sizes from 2/0 x 7/0 through 4/0 x 9/0

- Sand to 1.625

Profiled Particle Core: Sizes from 1/0 x 6/8 through 3/0 x 8/0

- Sand to 1-1/8" or 1-1/2"
- Can be profiled to accommodate any molded door face.

Lockblocks: Widths 3" or 3-1/2", Lengths from 6-3/4" to 20".

- Sanded to 1.115 or 1.500

Mineral Core: Raw sizes up to 47-1/4" x 94-1/2"

- Cut-to-size, sanded, glue-sizing.
- "Cool Core™" for metal temperature rise door manufacturing.

Banded Mineral Core: Neutral and positive pressure, 45-60-90 minute approvals

Profiled Mineral Core: Neutral and positive pressure, 45-60 minute approvals

- Profiled "Cool Core" for embossed metal temperature rise doors.

Crossbanded Mineral Core: Neutral and Positive pressure, 45-60-90 minute approvals

Fire Door Components: Stiles and blocking material. Mixed orders are always available